



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DLE-033-775 REV: 1.0

T-1 3/4 (5mm) Round Shape LEDs

MODEL NO : 333-2UGC/H2/S745 ECN : Page: 1/4


■ Features :

- Popular T-1 3/4 diameter package.
- Choice of various viewing angles.
- Available on tape and reel.
- Reliable and robust.

■ Description :

- The series is specially designs for applications requiring higher brightness than that achievable with standard lamp.
- The LED lamps are available with different colors,intensities, epoxy colors, etc.

■ Package Dimension:



■ Applications :

- TV Set
- Monitor
- Telephone
- Computer

■ NOTES :

- 1.All dimensions are in millimeters.
- 2.An epoxy meniscus may extend about 1.5mm(0.059") down to the lead.

PART NO	CHIP		Lens Color
	Material	Emitted Color	
333-2UGC/SH2/S745	AlGaInP	Super Green	Water Clear

DESIGNER	CHECKER	APPROVER

B992348,991201

Office : NO 25,Lane 76,Chung Yang Rd,Sec.3

Tucheng,Taipei 236,Taiwan,R.O.C.

TEL : 886-2-2267-2000,2267-9936(22 Lines)

FAX : 886-2-2267-6189



EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DLE-033-775 REV: 1.0

T-1 3/4 (5mm) Round Shape LEDs

MODEL NO : 333-2UGC/H2/S745 ECN : Page: 2/4

■ Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Rating	Unit
Forward Current	If	40	mA
Operating Temperature	Topr	-40 to +85	°C
Storage Temperature	Tstg	-40 to +100	°C
Soldering Temperature	Tsol	260 ± 5	°C
Power Dissipation	Pd	100	mW
Peak Forward Current(Duty 1/10 @ 1KHZ)	If(Peak)	180	mA
Reverse voltage	Vr	5	V

■ Electronic Optical Characteristics :







Parameter	Symbol	MIN.	TYP.	MAX.	Unit	Condition
Luminous intensity	Iv	630.0	1000.0	----	mcd	If=20mA
Viewing Angle	2 θ 1/2	----	22	----	deg	If=20mA
Peak Wavelength	λ p	----	573	----	nm	If=20mA
Dominant Wavelength	λ d	----	571	---	nm	If=20mA
Spectrum Radiation Bandwidth	△ λ	----	20	-----	nm	If=20mA
Forward Voltage	Vf	1.6	2.3	2.7	V	If=20mA
Reverse Current	Ir	----	----	10	μ A	Vr=5V



T-1 3/4 (5mm) Round Shape LEDs

MODEL NO 333-2UGC/H2/S745ECN : Page: 3/4

■ Typical Electro-Optical Characteristic Curves





EVERLIGHT ELECTRONICS CO.,LTD.

Device Number : DLE-033-775

REV: 1.0

T-1 3/4 (5mm) Round Shape LEDs

MODEL NO 333-2UGC/H2/S745

ECN :

Page: 4/4

■ Reliability test items and conditions

NO	Item	Test Conditions	Test Hours/Cycle	Sample Size	Ac/Re
1	Soldering Heat	TEMP : 260°C ± 5 °C	10±1 SEC	76 Pcs	0/1
2	Solderability	TEMP : 230°C ± 5 °C	5±1 SEC	76 Pcs	0/1
3	Temperature Cycle	H : +85°C 30min ∫ 5 min L : -55°C 30min	50 CYCLE	76 Pcs	0/1
4	Thermal Shock	H : +100°C 5min ∫ 10 sec L : -10°C 5min	50 CYCLE	76 Pcs	0/1
5	High Temperature Storage	TEMP : 100°C	1000 HRS	76 Pcs	0/1
6	Low Temperature Storage	TEMP : -55°C	1000 HRS	76 Pcs	0/1
7	DC Operating Life	If = 20 mA	1000 HRS	76 Pcs	0/1
8	High Temperature / High Humidity	85°C/85% RH	1000 HRS	76 Pcs	0/1